

Budget Survey Tripleband GNSS Antenna (IP66)

Includes:

- Budget Survey GNSS Tripleband antenna (IP66)
- 2.5m pigtail cable with TNC to SMA connector



More info about the product!



Budget Survey Tripleband GNSS Antenna (IP66) SKU is: AS-ANT3B-BUDSUR-L1L2L5-25SMA-00

Get a discounted bulk price on this product for orders of 50 units or more. Contact us at info@ardusimple.com to get a quote.



Description

Survey grade and low cost Triple band (L1, L2, L5) active GNSS antenna with TNC connector and 2.5m cable terminated with SMA male. Supports GPS, GLONASS, Galileo, and BeiDou. Perfect match for Septentrio Mosaic-X5 and Unicorecomm UM980 boards.

Good to know:

- Compatible with all ArduSimple GNSS and RTK boards as well as any other multiband GNSS receiver in the market.



Specifications

3B Survey Budget antenna

Antenna element

Supported positioning signal bands:

o GPS: L1, L2, L5

o GLONASS: G1, G2, G3

o BeiDou: B1, B2, B3

o Galileo: E1, E5

o QZSS: L1, L2

Navic: L5

SBAS: WAAS, EGNOS, MSAS, GAGAN and SouthPAN

Polarization: RHCP

• Peak gain: 5dBi

• Axial Ratio @ zenith: <3dB

• Azimuth Coverage: 360 degrees

• Impedance: 50 ohm

• Phase center error: ±3mm

Electrical

Supply voltage: 3-5.5V

• Typical supply current @ 3V: 50mA

• Average LNA gain: 40dB

Maximum Noise Figure: 1.5dB

• Maximum VSWR: 2

Mechanical

Maximum length: 147mm

• Weight: 390g

• Mounting style: Magnetic base (requires accessory) or 5/8" x 11TPI thread

Connector: TNC female

• Cable length: Includes 2.5 meter cable terminated in SMA male

Environmental

• Operating Temperature: -40 to +85°C


• Storage Temperature: -40 to +85°C

 IP Rating: IP66 (excluding air vent in screw hole, which can be sealed when installed)

• RoHS: Yes



Image Gallery











Documentation

User Guide https://staging.ardusimple.com/gps-gnss-antenna-installation-guide/

Download CAD https://staging.ardusimple.com/wp-content/uploads/2024/08/AS-

model ANT3B-BUDSUR-L1L2L5-25SMA-00-R00.step

Budget Survey Tripleband GNSS Antenna (IP66) includes free basic technical support. Contact info@ardusimple.com for more information.

Data and descriptions in this document are subject to change without notice. Product photos and pictures are for illustration purposes only and may differ from the real product appearance.